



L&R Manufacturing Company

577 Elm Street, P.O. Box 607, Kearny, New Jersey 07032-0607 USA

Phone: 201-991-5330, Fax: 201-991-5870

E-mail: info@LRultrasonics.com, www.LRultrasonics.com

TELETYPEWRITER

Disassembly and hand scrubbing of components of teletypewriters and similar office machines is costly in terms of labor and necessary skills. An L&R Ultrasonic Cleaning System will clean these complex machines with only a few minor, delicate parts to be removed. Simply-

1. Remove shroud, ink pots, ribbons, etc. before cleaning. Do not disassemble units.
2. Place entire operating unit into Basket or Rack and immerse in tank #1 containing L&R #222 Non-Ammoniated Ultrasonic Instrument Cleaning Solution.
3. Cavitate for 4-6 minutes, lift out and drain (60 seconds).
4. Place unit into tank #2 containing Instrument Rinsing Solution.
5. Cavitate 4-6 minutes, lift out, drain and air dry.
6. Lubricate.

EQUIPMENT NEEDED:

Machines, Accessories*: Two Ultrasonic Cleaning Systems (4100 Series or equivalent) with Basket or Rack.

Solutions: #222 Non-Ammoniated Ultrasonic Instrument Cleaning Solution (Product Code 191); Instrument Rinsing Solution (Product Code 194).

*Recommended Ultrasonic Cleaning System varies as to internal tank dimensions and volume of required cleaning.