

SAFETY DATA SHEET

1. Identification of Substance and Manufacturer:

ELLANAR DELUXE JEWELRY CLEANER, PCN 296,297

Use: Ultrasonic jewelry cleaning solution, diluted as per instructions

Manufacturer: L&R Manufacturing Company, 577 Elm Street, P.O. Box 607 Kearny, NJ 07032-0607 USA.

Publication Date: 05/04/2018 REV: J

Product information call 201-991-5330 www.lrultrasonics.com

For emergencies involving a spill, leak fire or accident contact CHEMTEL 800-255-3924 within the United

States. Or 1-813-248-0585 for International calls

2. HAZARDS IDENTIFICATION



Warning! Irritant. May be harmful if swallowed.

Direct contact causes eye irritation. Prolonged skin contact causes redness and drying of the skin. Breathing high concentrations of vapors or mist causes irritation to the nose and drowsiness.

WARNING STATEMENT: Good industrial hygiene practices should be used when handling this material.

Acute Eyes: Direct contact causes irritation, redness and possible tearing.

Acute Skin: Prolonged or repeated contact causes redness, and drying of the skin.

Acute Inhalation: Breathing high concentrations of vapors or mist causes irritation to the nose and drowsiness.

Acute Ingestion: Not known, but would be expected to cause nausea and diarrhea.

POTENTIAL HEALTH EFFECTS:

Chronic Effects: This product does not contain any ingredient designated by IARC, NTP, ACGIH or OSHA as probable or suspected human carcinogen.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Component	CAS Number	Percentage
WATER	7732-18-5	80-90
ISOPROPYL ALCOHOL	67-63-0	1-5
OLEIC ACID	112-80-1	1-5
PINE OIL	8002-09-3	0.5-5
AMMONIUM HYDROXIDE SOLUTION	1336-21-6	1-7
SODIUM BICARBONATE	144-55-8	0.1-2.0
SODIUM TETRABORATE	1303-96-4	0.1-0.4
The exact concentration of composition has been withheld as a trade secret.		

4. FIRST AID MEASURES

Eye Exposure: Hold eyelids open and flush with a steady, gentle stream of water for at least 15 minutes. Seek medical attention.

Skin Exposure: Wash thoroughly with water. If irritation or redness develops, seek medical attention.

Inhalation: If respiratory irritation or distress occurs, move victim to fresh air. Seek medical attention if respiratory irritation or distress continues.

Ingestion: Seek immediate medical attention. DO NOT INDUCE VOMITING.

MEDICAL CONDITIONS POSSIBLY AGGRAVATED BY EXPOSURE: Skin contact may aggravate existing skin disease.

5. FIRE FIGHTING MEASURES

FIRE HAZARD DATA:

Suitable Extinguishing Media: Extinguish with dry chemical, CO2 or a BC/ABC extinguisher.

Special Fire Fighting Procedures: None known

Unusual Fire and Explosion Hazards: May be ignited by excess heat, sparks or flames. Closed containers may explode due to build up of pressure when exposed to extreme heat.

Hazardous Decomposition Materials: (under fire condition) Oxides of carbon and ammonia vapor.

6. ACCIDENTAL RELEASE MEASURES

Cleanup and Disposal of Spill: Ventilate area. Mop up spill and dispose of by dilution to a sanitary sewer system as permitted by local, state and federal regulations.

Regulatory Reporting: Not required

7. HANDLING AND STORAGE

Minimum/Maximum Storage Temperatures: 39 to 90°F. Protect from freezing.

HANDLING: AVOID CONTACT WITH SKIN, EYES OR CLOTHING

8. EXPOSURE CONTROL/PERSONAL PROTECTION

General: These recommendations provide general guidance for handling of this product. Because specific work environments and material handling practices vary, safety procedures should be developed for each intended application. When developing safe handling procedures, do

not overlook the need to clean and dispose of the material. Waste resulting from the use of this product should be handled in accordance with Section 13: Disposal Considerations.

Exposure Guidelines: Exposure limits are recommended worker breathing limits. The following limits apply to this material:

INGREDIENTS **LIMITS INGREDIENTS LIMITS** 400 PPM OSHA/ AACGIH TWA Oleic Acid None Established

Isopropyl Alcohol Pine oil 100 PPM ACGIH TWA 50 PPM (as ammonia) OSHA/PEL Ammonium hydroxide OEL-Australia TWA 0.1 ppm (.3 mg/m3) Water None established Sodium bicarbonate

Sodium Tetraborate 5 mg/m3 TWA **Engineering Controls:** Normal room ventilation.

Respiratory Controls: For reasonable uses of this material, respiratory protection should not be necessary.

Eye/Face Protection: Safety glasses to protect from splashing.

Skin Protection: Rubber or plastic gloves to avoid drying and irritation to the skin.

Work Practice Control: Normal hygiene in the work area should be taken when working with or handling this product.

9. PHYSICAL AND CHEMICAL PROPERTIES

Physical State: Hazy Liquid Color: Pink Odor: Ammonia Odor

Specific Gravity: 0.98 pH: Approximately 10.5 **Odor Threshold:** 5 ppm (ammonia) Water Solubility: Soluble Melting Point Range: Not available Evaporation Rate: Not Applicable

Freezing Point Range: Not established **Boiling Point:** 210-212 ° F Partition Coefficient; n-octanol / water: Not available

Vapor Pressure: Not established Vapor Density: Not established **Decomposition Temperature:** Not available Flash Point: None Method: Tag Closed Cup Auto Ignition Temperature: Not available Evaporation: Slight faster than water

Flammability limits (vol/vol %): Lower: No Data Upper: No Data Percent volatile by volume: Approximately 90% as water and alcohol **V.O.C.** (calculated): 0.26 lbs./ gal or 31.1 gm / 1.

10. STABILITY AND REACTIVITY

Chemical Stability: Stable

Conditions to be avoided: Heat and open flame

Materials/Chemicals to be avoided: Strong acids, strong oxidizing agents, aluminum.

Decomposition Type: Thermal: Oxides of Carbon and Nitrogen Possibility of Hazardous Reactions: WILL NOT OCCUR

11. TOXICOLOGICAL INFORMATION

Acute Eye Irritation: Irritating to eyes.

Acute Skin Irritation: No test data found for product. Acute Dermal Toxicity: No test data found for product. Acute Respiratory Irritation: No test data found for product. Acute Inhalation Toxicity: No test data found for product.

Acute Oral Toxicity: LD50 (rat) = 74 gm/kg .for oleic acid, 3200 mg/kg for pine oil

350 mg/kg for ammonium hydroxide 5045 mg/kg for isopropyl alcohol 4220 mg/kg for sodium bicarbonate 2660mg/kg for Sodium Tetraborate

Chronic Toxicity: This product does not contain any substances that are considered by OSHA, NTP, IARC OR ACGIH to be a probable or suspected human carcinogen. No additional test data was found for this product.

12. ECOLOGICAL INFORMATION

Ecotoxicological Information: No data found.

13. DISPOSAL CONSIDERATIONS

This product can, with dilution, be disposed in sanitary sewer system where permitted by local, federal and state regulations.

14. TRANSPORTATION INFORMATION

Not regulated. Do not stack cartons more than five high

15. REGULATORY INFORMATION

Inventory Issues: All components of this product are listed on the U.S. TSCA, Canadian DSL, European EINECS/ELINS chemical listings

16. OTHER INFORMATION

National Fire Protection Association

Hazard Rating, NFPA Health Flammability Reactivity Special 0 1

SDS CHANGES

DESCRIPTION OF CHANGE REV DATE **Emergency Contact Change** 05/04/2018

Disclaimer: The information herein is given in good faith but no warranty expressed or implied is made. This SDS has been prepared by L&R Manufacturing.